



Data Logging Solutions  
Australia & New Zealand

## HOBO® MX1101 Data Logger

Bluetooth low energy temperature and relative humidity data logger

Onset's HOBO MX1101 is a Low Energy (BLE) data logger that measures and transmits temperature and relative humidity data wirelessly to mobile devices via BLE Smart technology.


The self-contained wireless data logger, which works with Onset's free HOBOMobile® app for logger setup and data management, enables users to access data anytime from their mobile device over a 100-foot range. It communicates instantly and enables you to "cut the cord" by requiring no dedicated equipment beyond a mobile device for configuring the logger or reading out data. This saves considerable time and money.

### Supported Measurements:

Temperature, Relative Humidity, Dew Point

### Key Advantages:

- BLE enabled for use with mobile devices
- No internet access, cables, or computer required
- Download data any time from 100 ft. away
- Audible and visual alarms keep you notified of problems
- Easily share data and graph images for analysis



### Minimum System Requirements:



HOBOMobile



Mobile device



\*iOS 8.3, 8.4 & 9.0, or Android 4.4, 5.0, 5.1  
and Bluetooth 4.0 or later

► For complete information and accessories, please visit: [www.onsetcomp.com](http://www.onsetcomp.com)

<b>Part number</b>	<b>MX1101</b>
<b>Memory</b>	84,650 Measurements
<b>Sampling Rate</b>	1 second to 18 hours, user selectable
<b>Battery Life</b>	1 year, typical with logging rate of 1 minute and sampling interval of 15 seconds or greater, user replaceable, 2AAA
<b>Dimensions</b>	3.66 x 8.48 x 2.29 cm (1.44 x 3.34 x 0.9 in.)
<b>Temperature</b>	
<b>Range</b>	-20° to 70°C (-4° to 158°F)
<b>Accuracy</b>	±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)
<b>Resolution</b>	0.024°C at 25°C (0.04°F at 77°F)
<b>Response Time</b>	7.30 minutes in air moving 1 m/s (2.2 mph)
<b>Relative Humidity</b>	
<b>Range</b>	1% - 90%RH, non-condensing
<b>Accuracy</b>	±2.0% from 20%RH to 80%RH typical to a maximum of ±4.5% including hysteresis at 25°C (77°F); below 20%RH and above 80%RH ±6% typical
<b>Hysteresis</b>	±2% RH
<b>Resolution</b>	0.01%RH
<b>Response Time</b>	20 seconds to 90% in air moving of 1 m/s (2.2 mph)
<b>CE compliant</b>	Yes

Note: Temp & RH NIST certification services available for this product. Please visit [onsetcomp.com](http://onsetcomp.com), or call us at 1-800-564-4377.

## Contact Us

# HOB0<sup>®</sup>

Data Logging Solutions  
Australia & New Zealand

### Australia

**1300 186 107**

[sales@hobodataloggers.com.au](mailto:sales@hobodataloggers.com.au)

[www.hobodataloggers.com.au](http://www.hobodataloggers.com.au)

### New Zealand

**0800 104 904**

[sales@onetemp.co.nz](mailto:sales@onetemp.co.nz)

[www.onetemp.co.nz](http://www.onetemp.co.nz)